neo-fermit

Universal Type 2000/1
Suitable for Potable Water, Heating and Gas
For metal threaded connections in conjunction with hemp

No more dirty hands

⇒ Clean to use	⇒ Does not irritate skin	⇒ Does not dry up
⇒ Non-toxic	⇒ Solvent-free	⇒ Dismountable
⇒ Non-sticky	⇒ Non-shrinking	⇒ Environmentally Friendly
⇒ Non-staining	⇒ Non-hardening	

⇒ **neo-fermit Universal** is the ultimate thread sealing paste
⇒ Advantages include its ease of use, non-toxicity and high temperature rating
⇒ Versatile, neo-fermit Universal also works as a long lasting and effective lubricant
⇒ Comes in convenient easy squeeze 150g tube
⇒ Price comparable with equivalent products but more economical to use
⇒ Now readily available from Plumbing Merchants around New Zealand, ask for it by name

Area of Use:

Three products in one, suitable for potable water, heating and gas

Water: **Temperature range:** 0°C to +95°C / **Pressure:** 16 bar
Heating: **Temperature range:** 0°C to +130°C / **Pressure:** 7 bar
Gas: **Temperature range:** -20°C to +70°C / **Pressure:** 5 bar
Suitable for all types of gas including natural gas and liquefied petroleum gas in the gaseous phase

Manufactured in Germany to very high standards:

Preferred sealant for German Plumbers, in use for over 30 years

According to DIN EN 751-2 and DIN 30660 approved by DVGW (German Gas and Water Association) for domestic installation of gas and drinking water under: DVGW—Reg. No. NV-5142BM0052

Distributed by:
Fermit NZ Ltd
5 Garin Grove Richmond Nelson 7020
Ph/Fx 03 544 3213
info@fermit.co.nz
www.fermit.co.nz